

MATERIAL SAFETY DATA SHEET

For Welding Consumables and Related Products
Conforms to OSHA Hazard Communication Standard
29CFR 1910.1200
Standard Must Be Consulted for Specific Requirements

MSDS NO: SGP
REVISED 3-2006

SECTION I -- IDENTIFICATION

Manufacturer/Supplier: Washington Alloy Company
Address: 7010-G Reames Road, Charlotte, NC 28216

Telephone No: 704-598-1325
Emergency No: 704-598-1325

Trade Name: Superflow Liquid Soldering Flux Classification: Commercial Spec. A-A-51145C Form B

Family: Soldering Flux (Inorganic Acid)

SECTION II - COMPOSITION INFORMATION

Components	CAS Number	%	OSHA PEL
Ammonium Chloride	12125-02-9	4-15	NA
Hydrochloric Acid	7647-01-0	3-15	5PPM
Zinc Chloride	7646-85-7	30-45	1PPM

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

SECTION III - HEALTH HAZARDS

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove to Fresh Air or Administer Oxygen. Call Physician.

Eyes: Flush with Water for 10 Minutes. Call Physician.

Skin: Wash Thoroughly with Water.

Ingestion: If Patient is Fully Conscious, Rinse Mouth.
Obtain Medical Attention Immediately.

Primary Routes of Entry into Body: Fume Inhalation, Ingestion, Skin, and Eyes.

Symptoms of Overexposure: Pulmonary Edema, Abdominal Pain, Vomiting, Eye Damage and Skin Burn.

Medical Conditions Generally Aggravated by Exposure: None Presently Known.

Chemical Listed as Carcinogen or Potential Carcinogen: None

OSHA Permissible Exposure Limit (PEL): 1 ppm

ACGIH Threshold Limit Value (TLV): 1 ppm

H.M.I.S. Information: HEALTH = 3 FLAMMABILITY = 0 REACTIVITY = 0

EAST COAST
7010-G Reames Rd
Charlotte, NC 28216
Tel (888) 522-8296
Fax (704)598-6673

WEST COAST
8535 Utica Ave
Rancho Cucamonga, CA 91730
Tel(800)830-9033
Fax (909)291-4586



Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations and decisions and should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damaged incurred from the use of any information contained herein, in whole or in part.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: (Method Used): None **Flammable Limits:** Lower-NA, Upper-NA
Extinguishing Media: Dry Chemical, CO2 Foam /ABC **Auto Ignition Temperature:** None
Special Fire Fighting Procedures: Normal Caution When Using Chemicals
Unusual Fire and Explosion Hazards: Will Release Small Amounts of HCl upon Decomposition.

SECTION V - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Spilled: First Neutralize with Soda Ash or Sodium Bicarbonate, Dilute with Water and Dispose of in Accordance with EPA Regulations.

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is Stable
Conditions to Avoid: Excessive Heat or Cold, Incompatible Materials
Incompatibility: Alkaline, Strong Oxidizing or Reducing Materials, Cyanides or Combustible Materials
Hazardous Decomposition Products: HCl, Zinc Chloride, Zinc Oxide, Ammonium.
Hazardous Polymerization: Will Not Occur

SECTION VII - CONTROL MEASURES

Ventilation: Yes **Eye Protection:** Safety Glasses/ Goggles / Face shields as needed
Protective Gloves: Rubber or neoprene , NIOSH Approved
Mechanical (General): Yes **Local Exhaust:** Yes
Respiratory Protection (Type): NIOSH Approved Respirator.
Other Protective Clothing or Equipment: Rubber Apron

SECTION VIII - HANDLING AND STORAGE

Storage: Store in Plastic Containers in Cool Area.
Handling Precautions: Safe Precautionary Practices to Avoid Spills and Exposure to Skin and Fumes
Work/Hygienic Practices: Avoid Contact with Skin, Eyes and Clothing.
Other Precautions: Keep Container Away From Excessive Heat.

SECTION IX - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point: 104°C/220°F **Specific Gravity (Water = 1):** 1.32
Vapor Pressure (mm Hg): NA **Percent Volatile by Volume:** 64%
Vapor Density (Air = 1): NA **Evaporation Rate (Butyl Acetate = 1):** 0.6
Melting Point: Liquid **Solubility in Water:** Moderate to unlimited
Reactivity in Water: None **Appearance and Odor:** Clear, odorless liquid

SECTION X - TRANSPORTATION AND DISPOSAL CONSIDERATIONS

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.
Hazard Class: 8 **Packing Group:** III
Identification Number: UN 1760
Type D.O.T Label Required Information: Corrosive
Less than 1 gallon renamed and reclassified as Consumer Commodity –ORM-D (49CFR173.154C)
Waste Disposal Method: Dispose in Accordance with EPA Regulations.

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations and decisions and should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damaged incurred from the use of any information contained herein, in whole or in part .